Wall-mounted fancoils

BLFC-...-W-2-AC/1A

Air flow:
180–1250 m³/h

Cooling capacity:
1.35–7 kW

These models are compact in size and wall-mounted, which makes them ideal for apartments, offices, and hotels.



Key features

- Stylish design that suits any interior.
- Quiet operation, ensuring comfort in the room.
- High efficiency thanks to optimized heat exchange.
- Easy control via remote control.
- EC fans for lower energy consumption and smooth power adjustment.

Wall-mounted fancoils

Specification	Standard size		20	30	40	50	60	80
Air flow	High	m^3/h	340	510	680	850	1020	1250
	Medium	m^3/h	260	380	515	650	765	950
	Low	m^3/h	180	260	340	430	520	600
Cooling capacity	High	W	2200	3000	4000	4800	5700	7000
	Medium	W	1800	2500	3250	3900	4650	5700
	Low	W	1350	2100	2500	2950	3500	4200
Heating capacity	High	W	3500	4800	6400	7700	9200	11000
	Medium	W	2850	4000	5200	6250	7450	8950
	Low	W	2150	3350	4000	4750	5650	6800
Power supply			220 V / 50-60 Hz / 1 Ph					
Power consumption	W	High, 0 Pa	20	30	36	44	56	75
Noise level	dBA	High, 0 Pa	28	37	41	43	44	48
Water flow	m^3/h		0.38	0.51	0.68	0.82	0.97	1.2
Hydraulic pressure	kPa		13	21	21	28	25	35
Water inlet	-		ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"
Drain hole	-		ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"	ZG1/2"
Net dimensions (W/H/L)	mm		850*291*203	850*291*203	972*302*224	972*302*224	1081*327*248	1081*327*248
Net weight	kg		11	11	14.5	14.5	18	18

Note:
1. Cooling: air temperature 27 °C CT/19.5 °C BT; water temperature (inlet / outlet): 7/12 °C.
2. Heating: air temperature 21 °C; water temperature (inlet): 60 °C