

Auto 150

Extract fans

- Casing material: Plastic

	Unit of measurement	Auto 150
Minimum supply voltage	V	220
Maximum supply voltage	V	240
Power supply frequency	Hz	50
Maximum airflow	m^3/h	295
Ingress protection rating	-	IP24
Impeller material	-	Plastic

Dimensions

a	b1	b2	b3	c	∅ d	e
210	150	195	196	115	150	34


a
b1
b2
b3
c
e
d

Ecodesign

Trademark	Blauberg					
Model	Auto 150					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	-32	B	-15	E	-6	F
Type of ventilation unit	Unidirectional					
Type of drive installed	Multi-speed					
Type of heat recovery system	None					
Maximum flow rate (m³/h)	295					
Electric power input (W)	26					
Reference flow rate (m³/s)	0.057					
Specific power input (SPI) (W/(m³/h))	0.057					
Control typology	Manual control					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU UVU					
Sound power level (dB(A))	59					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	100		100		100	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	3400		1700		800	