

BLS09 RH 9000

Floor mounted heat recovery units

• Heat exchanger type: Rotary, condensation or enthalpy
• Heat exchanger material: Aluminium/aluminium with hygroscopic coating
• Sound-insulated casing
• Reheater: Optional
• Preheater: Optional
• BMS protocol: ModBus, Bacnet
• Control: Wired control panel
• Casing material: Aluzinc steel

	Unit of measurement	BLS09 RH 9000
Casing performance	-	50 mm, T2/TB2
Phases	-	3
Minimum supply voltage	V	380
Maximum supply voltage	V	480
Power supply frequency	Hz	50/60
Rated power supply fan	W	6x700
Rated power extract fan	W	6x700
Unit current (without electric heaters)	A	36.5
Maximum airflow	m^3/h	9850
Maximum airflow at ESP 200 Pa	m^3/h	9700
Heat exchanger type	-	Rotary, condensation or enthalpy
Heat exchanger material	-	Aluminium/aluminium with hygroscopic coating
Weight	kg	1610
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-25
Ambient air temperature max	°C	60
Ambient air temperature min	°C	-40
Ingress protection rating	-	IP22
Ingress protection rating of the drive	-	IP54

Dimensions