



KOMFORT ERV D 450 L S3


Suspended heat and energy recovery air handling units

- Heat exchanger type: Cross flow
- Heat exchanger material: Enthalpy
- Sound-insulated casing
- Enthalpy heat exchanger
- Control: Speed switch
- Casing material: Coated steel


	Unit of measurement	KOMFORT ERV D 450 L S3
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	50
Maximum airflow	m³/h	500
Heat recovery efficiency, max	%	87
Heat exchanger type	-	Cross flow
Heat exchanger material	-	Enthalpy
Weight	kg	39
Transported air temperature (max)	°C	40
Transported air temperature (min)	°C	-15
Ambient air temperature max	°C	40
Ingress protection rating	-	IP22
Ambient air humidity max	%	60
Ingress protection rating of the drive	-	IP44

Dimensions

D	B	H	L
150	704	227	1020



Ecodesign



Trademark	Blauberg					
Model	KOMFORT ERV D 450 L S3					
Specific energy consumption (SEC) (kWh/(m²/a))	Cold		Average		Warm	
	-47.9	A+	-14.6	E	7.1	G
Type of ventilation unit	Bidirectional					
Type of drive installed	Variable speed					
Type of heat recovery system	Recuperative					
Thermal efficiency of heat recovery (%)	73					
Maximum flow rate (m³/h)	450					
Electric power input (W)	340					
Reference flow rate (m³/s)	0.094					
Reference pressure difference (Pa)	50					
Specific power input (SPI) (W/(m³/h))	0.809					
Control typology	Manual control					
Maximum internal leakage rates (%)	2.7					
Maximum external leakage rates (%)	2.7					
Declared typology	RVU BVU					
Sound power level (dB(A))	57					
The annual electricity consumption (AEC) (kWh/a)	Cold		Average		Warm	
	1595		1058		1013	
The annual heating saved (AHS) (kWh/a)	Cold		Average		Warm	
	7904		4040		1827	

Accessories

Other accessories

Name	Photo	Description
FP 300x270x48 F8		F8 filter
FP 300x270x48 G4		G4 panel filter

SB C4 300/270		