

Tubo-F 350 4E

Inline axial fans

- Impeller type: Axial
- Casing material: Coated steel
- Installation in any position

	Unit of measurement	Tubo-F 350 4E
Phases	-	1
Maximum supply voltage	V	240
Minimum supply voltage	V	220
Power supply frequency	Hz	50/60
Maximum airflow	m³/h	2500
Weight	kg	8.4
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-30
Ingress protection rating	-	IPX4
Ingress protection rating of the drive	-	IP44
Impeller material	-	Coated steel


speed_1_50Hz
speed_1_60Hz
Static pressure [Pa]
100
50
0
0
1,000
2,000
Airflow [m3/h]


speed_1_50Hz
speed_1_60Hz
150
100
50
0
Power [W]
0
1,000
2,000
Airflow [m3/h]

Dimensions

Ecodesign

Trademark	Blauberg
Model	Tubo-F 350 4E
Type of ventilation unit	Unidirectional
Type of drive installed	External MSD or VSD
Type of heat recovery system	None
Nominal external pressure (Pa)	80
Maximum external leakage rates (%)	2.7
Static efficiency (%)	29.9
Effective electric power input (kW)	0.13
Sound power level (dB(A))	82
Declared typology	NRVU UVU